
# Hull Inspector (Tankship) (HT)



**PQS** Workbook

# HT Qualification Task Matrix

TSK#	TASK	DATE
CS02	Inspect bulk liquid cargo system.	
CS08	Inspect cargo pumproom(s).	
CS10	Inspect cargo tank vents.	
CS11	Inspect closed gauging systems.	
CS12	Ensure vessel's IGS/COW operations/equipment manual was reviewed.	
CS14	Inspect the COW equipment.	
CS15	Inspect the vessel's letter of acceptance for installed IGS/COW system.	
CS16	Inspect the vessel's IGS/COW operations/equipment manual entries.	
CS17	Examine IGS equipment and verify that it is properly installed.	
CS18	Witness IGS operational test of safety shutdowns and controls.	
CS19	Witness IGS operational test of visual and/or audible alarms.	
CS20	Witness operational test of IG blower shutdown for various conditions.	
CS21	Ensure gauging system is installed for the cargoes listed on the SOE.	
CS22	Inspect the cargo pipe valves, pump manifolds, and piping.	
CS26	Inspect the cargo transfer hoses for condition and required markings.	
FF15	Inspect fixed foam extinguishing systems.	
MI03	Determine if additional requirements for TV steering systems are met.	
PP08	Examine slop tank arrangement.	
PP09	Examine instruction manual for cargo and ballast systems.	
PP10	Examine records of discharge operations.	
PP11	Examine damage stability information.	
RT03	Complete HI qualification.	
VS01	Inspect ventilation system in pumproom(s).	
VS04	Inspect cargo tank vents.	

Trainee's OJT Manual has been reviewed and I recommend a training qualification board be scheduled.

Training Officer:	
Date:	
Date Qualification Board Completed:	

Task<br/>NumberOJT<br/>TaskDate<br/>CompletedVerifying<br/>OfficerCS02Inspect bulk liquid cargo system.

- Pumprooms and/or pumping equipment:
  - Lighting fixtures and all electrical equipment are explosion proof
  - No dead ended, loose or frayed cabling
  - No jury-rigged wiring, extension cords, etc.
  - Bulkheads gas tight
  - Ladders
  - Ventilation system complete and operating
  - Pumps and controls operational
  - No leaking seals
  - Mechanical and electrical remote operating devices attached and operational
- Cargo piping:
  - Piping
  - Valves
  - Fittings
  - Gaskets
  - Supports
  - Materiel condition of all components
  - Expansion joints
- Gauging and venting system:
  - Type of gauging (open, closed, restricted)
  - Gauging type approved for cargo carried
  - Gauging systems operational
  - High and low level alarms
  - Overfill controls
  - Condition of vent piping and vent masts
  - Vent outlets at proper height
  - Required valves installed and operational
  - Pressure relief valves tested and certified no signs of tampering
  - Pressure vacuum valves and headers free of corrosion or dirt
  - Flame screens installed and acceptable
- Vapor recovery system
- Bulk liquid cargo heating system:
  - Indicate which tanks
  - Separate from hotel services for toxic cargoes
  - Contamination detection available for toxic cargo
  - System operational
- Bulk liquid cargo inerting system

<u>Task</u> <u>Number</u>	<u>OJT</u> <u>Task</u>	<u>Date</u> <u>Completed</u>	<u>Verifying</u> <u>Officer</u>
CS02 (cont'd.)	<ul> <li>Operational procedures:         <ul> <li>Aboard vessel</li> <li>Procedures in compliance with applicable CFR parts</li> <li>Transfer system adequately described</li> <li>Shipping papers/manifest</li> </ul> </li> </ul>		
CS08	<ul> <li>Inspect cargo pumproom(s).</li> <li>Pumproom access doors open onto the weatherdeck</li> <li>Ladders and accesses allow individuals wearing breathing apparatus entry</li> <li>Hoisting system provided from the pump room to the main decks</li> <li>Discharge pressure gauge for each pump located outside the pump room</li> <li>Bilge pumping system with remote control and high level alarms provided</li> <li>Air changed with proper frequency by the power ventilation system</li> </ul>		
CS10	<ul> <li>Inspect cargo tank vents.</li> <li>Vent heights adequate and within CFR and IMO requirements</li> <li>Vents located properly with respect to discharge areas</li> <li>Drain traps installed</li> <li>PV valves set to lift at proper pressure</li> </ul>		
CS11	<ul> <li>Inspect closed gauging systems.</li> <li>High level alarms provided</li> <li>High level alarms have audible and visual indicators at the cargo control station</li> <li>Alarm level set within the limits proscribed by IMO or CFRs</li> </ul>		-
CS12	Ensure that vessel has an IGS/COW operations and equipment manual and that it has been reviewed by the Coast Guard or, after 1 JUN 82, by ABS.		
CS14	Inspect COW piping, valves and fittings, tank washing machines, pumps and stripping system to ensure they are properly constructed, installed, and maintained.  • Dirty ballast transfer pumps and piping  • Fixed piping for COW  • Oily residue tank  • Oil discharge/monitoring control system  • Coast Guard approved plans  • Permanently mounted COW machines and piping  • Overpressure relief valves		

<u>Task</u> <u>Number</u>	<u>OJT</u> <u>Task</u>	<u>Date</u> <u>Completed</u>	<u>Verifying</u> <u>Officer</u>
CS14 (cont'd.)	<ul> <li>Spectacle flanges</li> <li>One portable drive unit for each three COW machines</li> <li>Pumps of sufficient capacity to drive system</li> <li>Two or more pumps capable of supplying oil to the COW</li> <li>Stripping capacity in each tank 1.25 times the rate of the COW pumps</li> <li>Means to isolate stripping pump from cargo tank</li> <li>Pump monitoring device</li> </ul>		
CS15	Inspect the vessel's letter of acceptance for the installed IGS/COW system issued by the Coast Guard or ABS.		
CS16	Inspect the vessel's IGS/COW operations and equipment manual for entries for required inspections and details of operations conducted.		
CS17	Examine the following IGS equipment and verify that it is installed properly.  Flue gas isolation valve working Soot blower/flue gas interlock Gas scrubber with water seal and 2 sources of water supply Two blowers Shut-off valves on suction and discharge side of blowers The following instrumentation: IG temperature IG pressure Oxygen content in IG Means to calibrate instruments Automatic gas regulatory valve Two non-return devices Gas main isolation valve Deck water seal Pressure/vacuum protection Portable instruments to measure oxygen and flammable vapors Piping, drains		
CS18	Witness the IGS operational test of safety shutdowns and controls.  • Soot blower/fuel gas isolation valve interlock  • Automatic gas regulatory valve  - Upon blower failure  - Upon loss of water pressure to deck water seal  - Upon loss of control power  - Upon low water/high water in scrubber  - High IG temperature  • Backflow pressure test		

<u>OJT</u> <u>Task</u>	<u>Date</u> <u>Completed</u>	<u>Verifying</u> <u>Officer</u>
Witness IGS operational test of visual and/or audible alarms.		
<ul> <li>Low IG pressure</li> <li>Oxygen content in IG - move them 8%</li> <li>Loss of water supply to deck water seal</li> <li>High IG temperature</li> <li>Loss of water supply to scrubber</li> <li>High water level in scrubber</li> <li>IG blower failure</li> <li>Power failure to automatic gas regulating valve</li> <li>High IG pressure</li> </ul>		
Witness operational test of the IG blower shut down for the following conditions:  Loss of water supply to deck water seal High IG temperature		
<ul> <li>Low water level/flow in scrubber</li> <li>High water level in scrubber</li> <li>Remote outside of space</li> </ul>		
Ensure proper gauging system is installed for the cargoes listed on the cargoes and restrictions list (SOE).		
Inspect cargo system locations/equipment and determine if they meet the criteria specified in the regulations.		
<ul><li>Cargo pipe valving</li><li>Cargo pump manifolds</li><li>Cargo piping and hose connection manifolds</li></ul>		
Inspect the cargo transfer hoses for condition and required markings.		
Inspect fixed foam extinguishing systems.  Quantity of foam adequate for area protected The rate of application meets regulatory requirements Controls positioned properly Instructions posted Valves marked Foam has been analyzed: Specific gravity H Sediment content Water % Monitors and piping clear and function properly		
	Witness IGS operational test of visual and/or audible alarms.  Low IG pressure Oxygen content in IG - move them 8% Loss of water supply to deck water seal High IG temperature Loss of water supply to scrubber High water level in scrubber IG blower failure Power failure to automatic gas regulating valve High IG pressure Witness operational test of the IG blower shut down for the following conditions: Loss of water supply to deck water seal High IG temperature Low water level/flow in scrubber High water level in scrubber Remote outside of space Ensure proper gauging system is installed for the cargoes listed on the cargoes and restrictions list (SOE).  Inspect cargo system locations/equipment and determine if they meet the criteria specified in the regulations. Cargo pipe valving Cargo piping and hose connection manifolds Inspect the cargo transfer hoses for condition and required markings.  Inspect fixed foam extinguishing systems. Quantity of foam adequate for area protected The rate of application meets regulatory requirements Quantity of foam adequate for area protected The rate of application meets regulatory requirements Controls positioned properly Instructions posted Valves marked Foam has been analyzed: Specific gravity pH Sediment content Water %	Witness IGS operational test of visual and/or audible alarms.  Low IG pressure Oxygen content in IG - move them 8% Loss of water supply to deck water seal High IG temperature Loss of water supply to scrubber High water level in scrubber Ower failure Power failure to automatic gas regulating valve High IG pressure Witness operational test of the IG blower shut down for the following conditions: Loss of water supply to deck water seal High IG temperature Low water level/Iflow in scrubber High water level in scrubber Remote outside of space Ensure proper gauging system is installed for the cargoes listed on the cargoes and restrictions list (SOE).  Inspect cargo system locations/equipment and determine if they meet the criteria specified in the regulations. Cargo piping and hose connection manifolds Cargo piping and hose connection manifolds Inspect the cargo transfer hoses for condition and required markings.  Inspect fixed foam extinguishing systems. Quantity of foam adequate for area protected The rate of application meets regulatory requirements Controls positioned properly Instructions posted Valves marked Foam has been analyzed: Specific gravity PH Sediment content Water % Monitors and piping clear and function properly

<u>Task</u>	$\underline{OJT}$	<u>Date</u>	<u>Verifying</u>
<u>Number</u>	<u>Task</u>	<u>Completed</u>	<u>Officer</u>
MI03	Determine if additional requirements for tank vessel steering systems are met.  • For tank vessels 10,000 GT or greater  • For tank vessels 40,000 GT of greater		
PP08	Examine slop tank arrangement.		
PP09	Examine instruction manual for cargo and ballast systems.		
PP10	Examine records of discharge operations.		
PP11	Examine damage stability information.		
RT06	Complete SMI Introduction Course.		
VS01	Inspect ventilation system in pumproom(s).		
VS04	Inspect cargo tank vents.  • PV valves provided where required and function properly		

- Vent heights in compliance with regulations and international agreements
- Vents open onto safe/unsafe areas
- Vent header systems provided where required

DATE	LOCATION	VESSEL NAME	VESSEL CLASS	INSPECTION TYPE	LEAD INSPECTOR

### **NOTES**

DATE	LOCATION	VESSEL NAME	VESSEL CLASS	INSPECTION TYPE	LEAD INSPECTOR

### **NOTES**

DATE	LOCATION	VESSEL NAME	VESSEL CLASS	INSPECTION TYPE	LEAD INSPECTOR

# NOTES